



产品特点

- ◆ 四象限速度、电流控制.
- ◆ 内置电源, 直接对内部及外部电子元器件供电.
- ◆ 交流供电模式.
- ◆ 电枢电流反馈控制.
- ◆ 三相整流器.
- ◆ 紧凑结构.
- ◆ 操作方便.

技术参数

驱动器型号	输出电压	最大输出电流	额定输出电流	直流供电电压	额定输入电压	最小输入电压	最大输入电压
	U _A (V)	I _{max} (A)	I _{NRMS} (A)	U _{CCN} (VDC)	U _N (VAC)	U _{min} (VAC)	U _{max} (VAC)
MQC 0506	48	12	6	55	24.48VDC	16VDC	65VDC
MQC 0510	48	20	10	55	24.48VDC	16VDC	65VDC
MQC 0606	60	12	6	65	46	20	51
MQC 0608	60	16	8	65	46	30	51
MQC 0610	60	20	10	65	46	30	51
MQC 1206	120	12	6	125	90	30	98
MQC 1208	120	16	8	125	90	30	98
MQC 1210	120	20	10	125	90	30	98
MQC 1510	150	20	10	155	113	30	125
MQC 1515	150	30	15	155	113	30	125
1)注:MQC05XX必须直流供电.							

产品代码

